

Installation

Installation Requirements for Warranty Qualification

- Dig a hole a minimum of one foot larger than the tank
Tank MUST be placed on perfectly solid and level ground.
(Hole must not be high in the center) Use 1" washed rock for leveling.
The inlet side of the tank should be as close to the inlet trench as possible.
- Tank must not be filled with water until it completely backfilled.
- Keep tires 2 feet back from tank when backfilling.
- Tanks should be backfilled all around, evenly, in 2 foot intervals.
- Do not apply any pressure to the lid or to the 6" ABS pipe.
- Finish by mounding dirt over tank. Water will run off and dirt will settle.
- There must be no equipment or vehicle traffic allowed within 2 feet of the tank.
- Leave a minimum of 1 ft of water in any cistern or sewage holding tank that will be left unused, especially over the winter months.
- Warranty will not be honored if tank is not properly installed.

Warranty Policy

Pembina Concrete Products Ltd, offers a 15 year prorated warranty on tanks installed to our specifications.

Warranty covers 100% replacement cost if tank is proven to be defective within two years of installation.

Warranty after two years will be prorated at 10% yearly, on cost of the tank only.

Warranty applies to original owner and or original installation.

Costs for repair or replacement will require prior approval by Pembina Concrete

Products Ltd, to be considered for warranty coverage.

This warranty does not cover the replacement of any materials lost due to leakage or cost of damages resulting from leakage.

Pembina Concrete Products Ltd will not warranty any tanks damaged due to improper installation or usage.



Pembina Concrete Products

Delivery

Our fleet of tri drive rear mounted knuckle pickers can deliver products wherever your next job takes you. Our experienced drivers are the best in the business and can get your tank set no matter what the conditions.



Pick Up

If you have the equipment to pick up your own tank, we have a state of the art loading facility that allows you to drive in and out with minimal wait time.



Inventory

PCP is situated on 60 acres that allows us to keep many tanks of all models in stock and ready at a moments notice.



London Boulder


PCP is pleased to supply the London Boulder line of retaining wall systems. Strength meets quality in these easy to install blocks that can be used for both commercial and residential use.

LB42™

42" deep blocks
Multiple setbacks
Multiple face textures
Dual face walls
Free standing wall


LB42 - 42" Full Boulder

Dimensions: 48" x 18" x 42"
Weight: 2160 lbs.
Sq. Ft. / Block: 6 sq. ft.



LB42 - Cap Boulder

Dimensions: 48" x 18" x 38"
Weight: 1260 lbs.
Sq. Ft. / Block: 6 sq. ft.



LB42 - Right Cap Corner

Dimensions: 24" x 18" x 34"
Weight: 660 lbs.
Sq. Ft. / Block: 3 sq. ft.



LB42 - Left Cap Corner

Dimensions: 24" x 18" x 34"
Weight: 660 lbs.
Sq. Ft. / Block: 3 sq. ft.



LB42 - 90 Degree Return

Dimensions: 48" x 18" x 24"
Weight: 1250 lbs.
Sq. Ft. / Block: 9 sq. ft.



Sumps

PCP offers one and two - compartment garage/shop sumps. Complete with a solid lid, and or grate they are easily installed to complete your garage or shop floor.

2 Compartment Dimensions:

60" long

31" wide

39 ³/₄" tall

1 Compartment Dimensions:

30" long

31" wide

39 ³/₄" tall

For larger projects, such as car washes, PCP will customize a 750 gallon industrial sump on request.



Parking Curbs

Dimensions

8' long 7" wide 6" high

